



THE PERCOLA® DRIP-HOLES REPRESENT A MINIMUM OF 10% OF THE SURFACE AREA AND PROVIDE AN AREA IN EXCESS OF 0.025m<sup>2</sup>/m<sup>2</sup> WHEN FILLED WITH SUITABLE AGGREGATE.

THIS PRODUCT COMPLIES WITH BS EN 1338:2003 CONCRETE PAVING BLOCKS.

BLYKO PAVING PRODUCTS  
 MARITIME HOUSE  
 BASIN ROAD NORTH  
 HOVE  
 BRIGHTON  
 BN41 1WR

TEL: +44 (0) 1273 704970  
 FAX: +44 (0) 1273 597123

admin@blyko.co.uk  
 www.blykopavingproducts.co.uk



THIS DRAWING IS ALSO AVAILABLE IN DWG & DXF FORMATS.

THIS IS A SOLIDWORKS GENERATED DRAWING - DO NOT CHANGE MANUALLY

TOLERANCES  
UNLESS OTHERWISE STATED

0.00 ± 0.13	HOLE -0.03/+0.08
0.0 ± 2.00	
0 ± 2.00	ANGULAR ±30' (1/2°)

ALL DIMENSIONS IN mm  
 DIMENSIONS APPLY AFTER PLATING  
 DO NOT SCALE



GEOMETRIC TOLERANCE  
SYMBOLS TO BS 8888

STRAIGHTNESS	—
FLATNESS	▭
ROUNDNESS	○
PARALLELISM	∥
SQUARENESS	⊥
ANGULARITY	∠
POSITION	⊕
CONCENTRICITY	⊗
SYMMETRY	≡
RUN-OUT	↗
DATUM FEATURE	△

THIS DRAWING IS SUPPLIED IN CONFIDENCE AND MUST NOT BE REPEATED OR COMMUNICATED TO A THIRD PARTY WHOLLY OR IN PART WITHOUT PERMISSION IN WRITING FROM THE OWNERS.

©RENDO 2009  
 ALL RIGHTS RESERVED



DRAWN	M.PAYNE
DATE	07/06/09
ISSUE	A
SIZE	A3
SCALE	SCALE
CUSTOMER	BLYKO

Iliad House  
 Byfield Place  
 Bognor Regis  
 West Sussex  
 PO22 9QY  
 Tel: 02032 872378

